

SAFETY DATA SHEET

1. Identification

Product identifier	EXTRA STRENGTH CSP CLEANER
Other means of identification	
SDS number	548N-02B
Product code	HIL00125
Recommended use	Bathroom Cleaner
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/I	Distributor information
Manufacturer	
Manufacturer	
Company name	HILLYARD INDUSTRIES
Address	302 North Fourth St.
	St. Joseph, MO 64501
Contact person	Regulatory Affairs
Telephone number	(816) 233-1321 (Ext. 8285)
Fax	(816) 383-8485
E-mail	regulatoryaffairs@hillyard.com
Emergency telephone #	(800) 424-9300
	(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger	
Hazard statement	Causes severe skin burns and eye damage. Causes serious eye damage.	
Precautionary statement		
Prevention	Do not breathe mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
Hazard(s) not otherwise classified (HNOC)	None known.	
Supplemental information	Not applicable.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethylene glycol monobutyl ether		111-76-2	1 - < 3
Polyethylene Glycol		25322-68-3	< 0.1
Other components below reportable level	S		90 - 100

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician or poison control center immediately.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Chemical burns must be treated by a physician. Call a physician or poison control center immediately. For minor skin contact, avoid spreading material on unaffected skin.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Corrosive effects. May cause temporary blindness and severe eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures	
Suitable extinguishing media	Not applicable, non-combustible. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire. Not applicable, non-combustible.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment	None (non-combustible). Self-contained breathing apparatus and full protective clothing must be

and precautions for firefightersworn in case of fire.Fire fighting
equipment/instructionsMove containers from fire area if you can do so without risk.Specific methodsMove container from fire area if it can be done without risk.General fire hazardsNo unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	This product is miscible in water. Should not be released into the environment. Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills in original containers for re-use. For waste disposal, see section 13 of the SDS. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapor. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure. Do not get this material on clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling.

Conditions for safe storage, Store locked up. Store in original tightly closed container. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS). including any incompatibilities

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

US. OSHA Table Z-1 Limit Components	Туре	(,	Value	
Ethylene glycol monobutyl ether (CAS 111-76-2)	PEL			240 mg/m3	
				50 ppm	
US. ACGIH Threshold Lim					
Components	Туре			Value	
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA			20 ppm	
US. NIOSH: Pocket Guide					
Components	Туре			Value	
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA			24 mg/m3 -	
				5 ppm	
US. AIHA Workplace Envi Components	ronmental Exposure Lo Type	evel (WEEL) Guide		Value	Form
Polyethylene Glycol (CAS 25322-68-3)	TWA			10 mg/m3	Particulate.
Biological limit values					
ACGIH Biological Exposu	re Indices				
Components	Value	Determinant	Specimen	Sampling T	ime
Ethylene glycol monobutyl ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine urine	in *	
* - For sampling details, ple	ase see the source docu				
Exposure guidelines					
US - California OELs: Skin	n designation				
Ethylene glycol monob US - Minnesota Haz Subs	utyl ether (CAS 111-76-2 : Skin designation appl	,	absorbed thr	ough the skin.	
Ethylene glycol monob US - Tennessee OELs: Sk	utyl ether (CAS 111-76-2 in designation	2) Skin de	signation app	blies.	
Ethylene glycol monob US NIOSH Pocket Guide t	utyl ether (CAS 111-76-2 o Chemical Hazards: S		absorbed thr	ough the skin.	
Ethylene glycol monob US. OSHA Table Z-1 Limit	utyl ether (CAS 111-76-2 s for Air Contaminants			ough the skin.	
Ethylene glycol monob	utyl ether (CAS 111-76-2	2) Can be	absorbed thr	ough the skin.	
Appropriate engineering controls	should be matched to or other engineering	to conditions. If app controls to maintai	licable, use p n airborne lev	vels below recom	e used. Ventilation rates es, local exhaust ventilation, imended exposure limits. If o an acceptable level. Provide
ndividual protection measure					
Eye/face protection	Do not get in eyes.	Chemical goggles a	re recommer	nded.	
Skin protection					
Hand protection	Use protective glove Butyl rubber.	es made of: Nitrile. F	Rubber (natu	ral, latex). Neopro	ene. Polyvinyl chloride (PVC

Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using, do not eat, drink or smoke. Do not get this material on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Hazy, opaque, colorless liquid
Physical state	Liquid.
Form	Liquid.
Color	Colorless
Odor	Lemon odor
Odor threshold	Not available
рН	< 1
Melting point/freezing point	Not available
Initial boiling point and boiling range	195 °F (90.56 °C) corr.
Flash point	> 200.0 °F (> 93.3 °C) Tag Closed Cup
Evaporation rate	< 1 Ethyl ether = 1
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	17.5 mm Hg
Vapor density	0.6 Air=1
Relative density	1.09 at 77°F
Solubility(ies)	
Solubility (water)	Appreciable
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	9.08 lb/gal
Explosive limit	Not available
Percent volatile	78 - 83
VOC (Weight %)	1.11 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Reacts violently with strong alkaline substances. This product may react with reducing agents. Do not mix with other chemicals. Contact with incompatible materials.
Incompatible materials	Incompatible with bases. This product may react with reducing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful. May cause irritation to the respiratory system.	
Skin contact	Causes severe skin burns.	
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.	
Eye contact	Causes severe eye burns. Causes serious eye damage.	
Ingestion	Causes digestive tract burns.	
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.	

Information on toxicological effects

	. .	
Product	Species	Test Results
EXTRA STRENGTH CSP CLEAN	IER	
Acute		
Dermal	Dates	
LD50	Rabbit	8566.2949 mg/kg estimated
Inhalation LC50	Mauro	70000 ppm 7 Hours estimated
LC30	Mouse	70000 ppm, 7 Hours estimated
	Rat	45000 ppm, 4 Hours estimated
Oral		
LD50	Guinea pig	95975.2344 mg/kg estimated
	Mouse	80823.6328 mg/kg estimated
	Rabbit	31.8844 g/kg estimated
	Rat	6860.1733 mg/kg estimated
Components	Species	Test Results
Ethylene glycol monobutyl ether (CAS 111-76-2)	
Acute		
Dermal		
LD50	Rabbit	400 mg/kg
Inhalation		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
* Estimates for product may I	be based on additional component data not show	vn.
Skin corrosion/irritation	Causes severe skin burns and eye damage.	
Serious eye damage/eye irritation	Causes severe eye burns. Causes serious ey	ve damage.
Respiratory or skin sensitizatio	n	
Respiratory sensitization	Not available.	
Skin sensitization	This product is not expected to cause skin se	nsitization.
Germ cell mutagenicity	No data available to indicate product or any c mutagenic or genotoxic.	omponents present at greater than 0.1% are
Carcinogenicity	This product is not considered to be a carcino	ogen by IARC, ACGIH, NTP, or OSHA.

HIL00125 Version #: 02 Revision date: 03-31-2016 Issue date: 01-08-2015

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene glycol monobutyl ether (CAS 111-76-2)

US. OSHA Specifically Re	gulated Substances (29)	CFR 1910,1001-1050)
00. ConA opechically Re	guiateu oubstances (25 v	011111011011000

Not listed.

Not listed.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Prolonged inhalation may be harmful. Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

3 Not classifiable as to carcinogenicity to humans.

12. Ecological information

Ecotoxicity		of the low pH of this product, it would be e to aquatic organisms and aquatic system	expected to produce significant ecotoxicity upon s.
Product		Species	Test Results
EXTRA STRENGTH	CSP CLEANER		
Aquatic			
Crustacea	EC50	Daphnia	1247.9214 mg/l, 48 hours estimated
Fish	LC50	Fish	976.7318 mg/l, 96 hours estimated
Components		Species	Test Results
Polyethylene Glycol (CAS 25322-68-3)		
Aquatic			
Fish	LC50	Atlantic salmon (Salmo salar)	> 1000 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
14. Transport information	

DOT

UN number UN proper shipping name Transport hazard class(es)	NA1760 Compound Cleaning Liquid, n.o.s. (Phosphoric Acid)
Class	8

Subsidiary risk	-
Label(s)	8
Packing group	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions	None
ERG number	154
PACKAGES 1 GALLON AND	SMALLER ARE SHIPPED LIMITED QUANTITY OR ORM-D
ΙΑΤΑ	
UN number	UN1760
UN proper shipping name	Corrosive liquid, n.o.s. (Phosphoric Acid)
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	
Environmental hazards	No.
ERG Code	154
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
IMDG	
UN number	UN1760
UN proper shipping name	CORROSIVE LIQUID, N.O.S. (Phosphoric Acid)
Transport hazard class(es)	
Class	8
Subsidiary risk	-
Label(s)	8
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-A, S-B
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.





15. Regulatory information

15. Regulatory information	1	
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Co Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List or Exempt.	mmunication
TSCA Section 12(b) Export	Notification (40 CFR 707, Subpt. D)	
Not regulated.		
CERCLA Hazardous Substa	nce List (40 CFR 302.4)	
Not listed.		
SARA 304 Emergency relea	se notification	
	llated Substances (29 CFR 1910.1001-1050)	
Not listed.		
-	authorization Act of 1986 (SARA)	
Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No	
SARA 302 Extremely hazard	-	
Not listed.		
SARA 311/312 Hazardous chemical	No	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Safe Drinking Water Act (SDWA)	Not regulated.	
US state regulations		
US. California Controlled Su	ubstances. CA Department of Justice (California Health and Safety Code s	Section 11100)
Not listed.		
US. Massachusetts RTK - S	ubstance List	
Ethylene glycol monobut US. New Jersey Worker and	/l ether (CAS 111-76-2) Community Right-to-Know Act	
Ethylene glycol monobuty		
Ethylene glycol monobuty US. Rhode Island RTK	nd Community Right-to-Know Law /I ether (CAS 111-76-2)	
Not regulated.		
US. California Proposition 6	5	
California Safe Drinking \	Vater and Toxic Enforcement Act of 1986 (Proposition 65): This material is not sted as carcinogens or reproductive toxins.	known to contain
International Inventories		
Country(s) or region	Inventory name C	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	nents of this product comply with the inventory requirements administered by the govern components of the product are not listed or exempt from listing on the inventory admini	
16. Other information, inc	uding date of preparation or last revision	
Issue date	01-08-2015	
Revision date	03-31-2016	
Version #	02	
HMIS® ratings	Health: 3	
	Flammability: 0 Physical hazard: 0	

Disclaimer	No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products.
Revision Information	Composition / Information on Ingredients: Disclosure Overrides Physical & Chemical Properties: Multiple Properties Physical and chemical properties: Appearance