Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 1/11 Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)



Identification

Product identifier used on the label is either:

45 Ib. DAMTITE MAXIMUM COVERAGE POWDER WATERPROOFER, GRAY

Recommended use of the chemical and restriction on use

Recommended use*: for homeowner, contractor, industrial or professional users

Details of the supplier of the safety data sheet

Company:

WALL FIRMA, INC. 733 E. MAIN ST, MONONGAHELA, PA 15063 USA PH: 724.258.7175

Emergency telephone number CHEMTREC: 1-800-424-9300

Other means of identification

Chemical family: No data available

1. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irritation 2 Skin corrosion/irritation

Eye Dam./Irritation 1 Serious eye damage/eye irritation

Carcinogin:. 1A Carcinogenicity

STOT SE 3 Specific target organ toxicity — single exposure

(irritating to

respiratory system)

STOT RE 1 Specific target organ toxicity — repeated exposure

Label elements

Pictogram:



^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, expressor implied, including by incorporation into or reference in the seller's sales agreement.

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 2/11 Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

Hazard Statement:

H318 Causes serious eye damage.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H350 May cause cancer.

H372 Causes damage to organs (lung) thru prolonged orrepeated

exposure

Precautionary Statements (Prevention):

P280 Wear protective gloves/protective clothing/eye protection/face

protection.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe dust/gas/mist/vapors.

P202 P202 Do not handle until all safety precautions read and

understood.

P270 Do not eat, drink or smoke when using this product.

P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses,

if present and not difficult to remove. Keep rinsing eye.

P310 Immediately call a POISON CENTER or doctor/physician.

P304 + P304 + P340 IF INHALED: Remove person to fresh air & keep

comfortable for

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash before reuse.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection

point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

2. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Content (W/W)	Chemical name
14808-60-7	>= 10.0 - < 50.0 %	crystalline silica
65997-15-1	>= 25.0 - < 50.0	Cement, Portland, chemicals
1305-62-0	>= 1.0 - < 3.0 %	Calcium di-hvdroxide
13463-67-7	>= 0.3 - < 3.0 %	Titanium dioxide

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 3/11 Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

13397-24-5 >= 0.3 - < 3.0 % Gvpsum(Ca(SO4).2H2O)

1317-65-3 >= 0.0 - < 3.0 % Limestone

3. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

After inhalation of dust, keep patient calm, remove to fresh air. If difficulties occur: obtain medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labeling (see section 2) and/or in section 11.

Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no

known specific antidote.

4. Fire-Fighting Measures

Extinguishing media

Suitable extinguishingmedia:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Additional information:

Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 4/11
Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

Special hazards arising from the substance or mixture

Hazards duringfire-fighting:

carbon monoxide, carbon dioxide, harmful vapors

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire. Product is not combustible or explosive.

Advice for fire-fighters

Protective equipment for fire-fighting:

Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Product itself is non-combustible; consider fire-extinguishing method of surrounding areas. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

5. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid contact with skin and eyes. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of. Pack in tightly closed containers for disposal.

For residues: Rinse with plenty of water.

Avoid raising dust.

6. Handling and Storage

Precautions for safe handling

Avoid dust formation. Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion: No special precautions necessary.

Conditions for safe storage, including any incompatibilities

Segregate from metals. Segregate from acids. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Suitable materials for containers: High density polyethylene (HDPE)

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 5/11
Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

Calcium di-hydroxide	OSHA PEL	PEL 5 mg/m³ Respirable fraction; PEL 15 mg/
	ACGIH TLV	m³ Total dust ; TWA value 5 mg/m³ ; TWA value 5 mg/m³
Limestone	OSHA PEL	PEL 5 mg/m³ Respirable fraction; PEL 15 mg/m³ Total dust; TWA value 15 mg/m³ Total dust; TWA value 5 mg/m³ Respirable fraction
Gypsum (Ca(SO4). 2H2O)	OSHA PEL	PEL 5 mg/m³ Respirable fraction; PEL 15 mg/m³ Total dust; TWA value 15 mg/m³ Total dust; TWA value 5 mg/m³ Respirable fraction; ACGIH TLV TW value 10 mg/m³ Inhalable fraction;
Titanium dioxide	OSHA PEL	PEL 15 mg/m³ Total dust; TWA value 10 mg/m³
	ACGIH TLV	Total dust TWA value 10 mg/m ³
Crystalline Silica	OSHA PEL	TWA value 2.4 millions of particles per cubic footof air Respirable; The exposure limit is calculated from the equation, 250/(%SiO2+5) using a value of 100% SiO². Lower percentages of SiO² will yield higher exposure limits. TWA value 0.1 mg/m3 Respirable; The exposure limit is calculated from the equation 0/(%SiO²+2), using a value of 100% SiO². Lower percentages of SiO² will yield higher exposure limits. TWA value 0.3 mg/m³ Total dust; The exposure limit is calculated from the equation, 30/(%SiO²+2), using a value of 100% SiO². Lower percentages of SiO² will yield higher exposure limits.
		TWA value 0.025 mg/m³ Respirable fraction
Cement, Portland, chemicals	OSHA PEL	PEL 15 mg/m³ Total dust; EL5 mg/m³ Respirable fraction
	ACGIH TLV	TWA value 1 mg/m³ Respirable fraction;
	· _ ,	The value is for particulate matter containing

asbestos and <1% crystalline silica.

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 6/11 Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Use breathing protection if dusts are formed.

Hand protection:

Chemical resistant protective gloves, Manufacturer's directions for use should be observed because of great number of type gloves.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygienemeasures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Contaminated equipment or clothing should be cleaned after each use or disposed of.

8. Physical and Chemical Properties

Form: powder
Odor: earthv
Odor threshold: Not

Color: various colours

pH value: approx. 12 (approx. 20 °C) as aqueous suspensions

Melting temperature: >

Boiling temperature: not applicable

Sublimation point: No applicable information available.

Flash point: The substance/product isnon-combustible

Flammability:

Lower explosion limit: We do not expect any hazard as long as product is used

appropriately for applications intended on label and TDS

Upper explosion limit: not applicable

Auto-ignition: No applicable information available. Vapor pressure: No applicable information available.

Density: 2.7 g/cm³
Relative density: 2.70
Bulk density: 2,700 kg/m³

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 7/11
Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

168.6 lb/ft3

Vapor density: No applicable information available.

Thermal decomposition: No decomposition if stored and handled as prescribed & indicated.

Viscosity, dynamic: No applicable information available Viscosity, kinematic: No applicable information available.

Solubility in water: (20 °C) dispersible
Miscibility with water: (20 °C) not soluble
Solubility (quantitative): Not applicable
Evaporation rate: Not applicable

9. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Strong bases are formed on the addition of water.

Conditions to avoid

Avoid dust formation. Avoid humidity.

Incompatible materials

strong bases, strongacids

Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

10. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Product may present a nuisance dust hazard. Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficulties.

Oral No applicable information available.

Inhalation No applicable information available

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 8/11
Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

Dermal No applicable information available

Assessment other acute effects

Assessment of STOT single: Causes

temporary irritation of respiratory tract

The product has not been tested. The statement has been derived from the properties of the individual components.

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes. The product has not been tested. The statement has been derived from the properties of the individual components.

Skin

Result: Irritant.

Information on: Cement, Portland, chemicals Species:

rabbit Result: Irritant.

<u>Eye</u>

Result: Risk of serious damage to eyes.

Information on: Cement, Portland, chemicals Species: rabbit Result:

Severely irritating.

Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential. The product has not been tested. The statement has been derived from the properties of the individual components. Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-life is unlikely.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

<u>Genetic toxicity</u>

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: This product contains crystalline silica (quartz).

Information on: crystalline silica

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosolsis classified by the German MAK commision as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic

effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 9/11
Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

Information on: Titanium dioxide

Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

11. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

The product gives rise to pH shifts. Based on available Data, the classification criteria are not met.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Inorganic product which cannot be eliminated from water by biological purification processes. The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Experience shows this product to be inert and non-degradable Elimination information not

applicable

Bio-accumulative potential

Assessment bioaccumulation potential

The product will not be readily bioavailable due to its consistency and insolubility in water.

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 10/11 Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface.

Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is notexpected.

Additional information

Other eco-toxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

12. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/ groundwater.

Container disposal:

Completely emptied packaging can be given for recycling.

13. Transport Information

Land transport

USDOT Not classified as a dangerous good under transport regulation

Sea transport

IMDG Not classified as a dangerous good under transport regulation

Air transport

IATA/ICAO Not classified as a dangerous good under transport regulations

14. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

Registration status based on supplier confirmation

EPCRA 311/312 (Hazard categories): Acute; Chronic

State regulations

CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NFPA Hazard codes:

Health: 3 Fire: 0 Reactivity: 0 Special:

Damtite Powder Waterproofers & Waterproof Coatings

Revision date: 2015/05/01 Page: 11/11 Version: 001 (02000/SDS-Gray PowderWtrpfrs-US/EN)

15. Other Information

SDS Prepared by:

WALL FIRMA, INCORPORATED ProductRegulations SDS Prepared on: 2015/05/01

We support worldwide End-User Care initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAYAFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE, PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

END OF SAFETY DATA SHEET