MSDS 0223

\_\_\_\_\_\_ Section 1 -- PRODUCT AND COMPANY IDENTIFICATION HMIS CODES PRODUCT NAME 2. Health K.O. Dirt Blaster (TM) Flammability Reactivity PRODUCT CODES PPI 88438 CHEMICAL FAMILY Organic USE Cleaner & Degreaser MANUFACTURER'S NAME EMERGENCY TELEPHONE NO. The RectorSeal Corporation Chemtrec 24 Hours (800) 424-9300 2601 Spenwick Drive Houston, Texas 77055 USA DATE OF PREPARATION TECHNICAL SERVICE TELEPHONE NO. August 15, 2003 (800) 231-3345 \_\_\_\_\_\_ Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS \_\_\_\_\_\_ % by WT CAS No. INGREDIENT UNITS 75-09-2 Methylene Chloride ACGIH TLV 50 ppm 25 ppm OSHA PEL OSHA STEL 125 ppm \_\_\_\_\_\_ Section 3 -- HAZARDS IDENTIFICATION \_\_\_\_\_\_ SUMMARY OF ACUTE HAZARDS Repeated inhalation may cause dizziness, nausea and CNS effects. May cause severe eye and skin irritation. ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS INHALATION Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, drowsiness, and nausea. Advanced may cause collapse, unconsciousness, coma and possible death due to respiratory failure. EYE CONTACT Contact with eyes may cause severe irritation. SKIN CONTACT Irritation and drying. INGESTION May cause irritation of the digestive tract. May cause central nervous system depression, characterized by excitement, followed by headache,

SUMMARY OF CHRONIC HAZARDS

Skin irritation, contact dermatitis, and defatting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin,

coma and possible death due to respiratory failure.

dizziness, and nausea. Advanced stages may cause collapse, unconsciousness,

respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

### Section 4 -- FIRST AID MEASURES

-----

If INHALED: If overcome by exposure, remove victim to fresh air

immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt

action is essential.

If on SKIN: Immediately wash with soap and water. Remove and wash

any contaminated clothing.

If in EYES: Flush eyes with large amounts of water for 15 minutes.

Get medical attention if irritation persists.

If SWALLOWED: If swallowed, call a physician immediately. Only induce

vomiting at the instruction of a physician. Never give

anything by mouth to an unconscious person.

### Section 5 -- FIRE FIGHTING MEASURES

-----

FLASH POINT LEL UEL None N/D N/D

Negative Flame Extension, (NFPA) Level 1 Aerosol

EXTINGUSING MEDIA

Foam, dry chemical, CO2, or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and full body protective clothing. Hazardous decomposition products possible (see Section 10). Evacuate area. Dike area as run-off may create additional environmental contamination. UNUSUAL FIRE AND EXPLOSION HAZARDS: Aerosol cans are under pressure -

exposure to temperatures above 120F can cause bursting or "rocketing" of cans.

-----

### Section 6 -- ACCIDENTAL RELEASE MEASURES

\_\_\_\_\_\_

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use absorbent materials to prevent footing hazard and to contain. Ventilate area with forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

\_\_\_\_\_\_

#### Section 7 -- HANDLING AND STORAGE

-----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Shake well before using. Keep away from heat and open flames. Prolonged exposure to direct sunshine or

storage above 120 F may cause can to burst. Do not puncture or incinerate can.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing.

Empty containers may contain residues; treat as if full and observe all products precautions.

\_\_\_\_\_\_

# Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

\_\_\_\_\_\_

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion proof MECHANICAL (GENERAL): Acceptable OTHER: N/A PROTECTIVE GLOVES: Wear rubber gloves. EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent) OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical resistant coveralls recommended. WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse. \_\_\_\_\_\_ Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES \_\_\_\_\_\_ BOILING POINT: 104 F (40 C)@ 760mm Hg SPECIFIC GRAVITY (H20 = 1): 1.27 VAPOR PRESSURE (mm Hg): 350 mm HG @ 20 C MELTING POINT: VAPOR DENSITY (AIR = 1): 2.9 EVAPORATION RATE (ETHYL ACETATE = 1): >1 APPEARANCE/ODOR: Clear Liquid / Citrus Odor SOLUBILITY IN WATER: Insoluble \_\_\_\_\_\_ Section 10 -- STABILITY AND REACTIVITY STABILITY: Stable CONDITIONS TO AVOID: Do not store in temperatures above 120 F. INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers, acids and bases. HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO, and fragmented hydrocarbons. HAZARDOUS POLYMERIZATION: Will not occur. \_\_\_\_\_\_ Section 11 -- TOXICOLOGY INFORMATION CHRONIC HEALTH HAZARDS No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Methylene chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. .\_\_\_\_\_ TOXICOLOGY DATA Ingredient Name \_\_\_\_\_\_ Methylene Chloride Oral-Rat LD50:1600 mg/kg Inhalation-Rat LC50:88,000 mg/m3/30M \_\_\_\_\_\_ Section 12 -- Ecological Information

ECOLOGICAL DATA

Ingredient Name

\_\_\_\_\_\_

Methylene Chloride

Food Chain Concentration Potential None WATERFOWL TOXICITY N/AN/AAQUATIC TOXICITY

\_\_\_\_\_\_

Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Aerosols

Disposal Method: Empty containers can be disposed of in trash. Full containers should be depressurized to separate liquid phase. The liquid phase is considered a U080 waste and should be incinerated. Dispose of all liquid waste in accordance with all local, state and federal regulations.

\_\_\_\_\_\_

## Section 14 -- TRANSPORTATION INFORMATION

\_\_\_\_\_\_

DOT: Aerosols, Class 2.2, UN 1950, ERG#126

OCEAN (IMDG): Aerosols, Class 2.2, UN 1950, IMDG#2102, EMS#2-13

AIR (IATA): Aerosols, Class 2.2, UN 1950, ERG#126

WHMIS (CANADA): Class A, (Class D Division 1, Subdivision B)

\_\_\_\_\_\_

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA Ingredient Name

\_\_\_\_\_

Methylene Chloride

SARA 313 Yes

TSCA Inventory Yes
CERCLA RQ 1000 lbs.
RCRA Code U080

RCRA Code

\_\_\_\_\_\_

#### CALIFORNIA PROPOSITION 65

This product contains methylene chloride known to the state of California to cause cancer and/or birth defects or reproductive harm.

\_\_\_\_\_\_

### Section 16 -- OTHER INFORMATION

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further

information: (713) 263-8001