



SUPERPAINT[®]

Exterior Latex High Gloss A85 Series

As of 06/30/2015, Complies with:			
OTC	Yes	LEED [®] 09 CI	N/A
SCAQMD	No	LEED [®] 09 NC	N/A
CARB	Yes	LEED [®] 09 CS	N/A
CARB SCM 2007	Yes	LEED [®] H	N/A
MPI	-	NGBS	N/A

CHARACTERISTICS

SuperPaint Exterior Latex High Gloss, with improved resistance to early dirt pick up, provides outstanding performance on properly prepared aluminum and vinyl siding, wood, hardboard, masonry, cement, brick, block, stucco, and metal.

VinylSafe™ Color Technology allows the use of many darker colors on vinyl siding that cannot be made in most other coatings.

Recommended for:

- Doors
- Trim
- Windows
- Shutters

Excellent Performance in:

- Block Resistance
- Moisture Resistance
- Gloss Retention
- Flow and Leveling

Color: Most colors
To optimize hide and color development, always use the recommended P-Shadow primer

Coverage: 350 - 400 sq ft/gal
@ 4 mils wet: 1.8 mils dry

Drying Time, @ 77°F, 50% RH:
Touch: 1 hour
Tack Free: 4 hours
Recoat: 18 hours

Drying and recoat times are temperature, humidity, and film thickness dependent

Flash Point: N/A

Finish: 70+ units @ 60°

Tinting with CCE:

Base	oz/gal	Strength
Extra White	0-5	100%
Deep Base	4-12	100%
Ultradeep Base	4-12	100%

Vehicle Type: Acrylic

Extra White A85W00051

VOC (less exempt solvents): 90 g/L; 0.75 lb/gal
As per 40 CFR 59.406 and SOR/2009-264, s.12

Volume Solids: 44 ± 2%

Weight Solids: 53 ± 2%

Weight per Gallon: 9.87 lb

Mildew Resistant

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

SPECIFICATIONS

SuperPaint Exterior Latex High Gloss can be self-priming when used directly over existing coatings, or bare drywall, plaster and masonry (with a cured pH of less than 8). The first coat acts like a coat of primer and the second coat provides the final appearance and performance. Please note that some specific surfaces require specialized treatment.

Aluminum & Aluminum Siding, Galvanized Steel, Vinyl Siding

2 cts. SuperPaint Exterior Latex
Concrete Block, CMU, Split face Block

1 ct. Loxon Block Surfacer
2 cts. SuperPaint Exterior Latex
Brick

1 ct. Loxon Conditioner
2 cts. SuperPaint Exterior Latex
Cement Composition Siding/Panels

1 ct. Loxon Concrete & Masonry Primer or Loxon Conditioner
2 cts. SuperPaint Exterior Latex
Stucco, Cement, Concrete

1 ct. Loxon Concrete & Masonry Primer
2 cts. SuperPaint Exterior Latex
Plywood

1 ct. Exterior Latex Wood Primer
2 cts. SuperPaint Exterior Latex
Wood (Cedar, Redwood)¹

1 ct. Exterior Oil-Based Wood Primer
2 cts. SuperPaint Exterior Latex

¹ Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. For best results on these woods, use a coat of Exterior Oil-Based Wood Primer.

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

SURFACE PREPARATION

WARNING! Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Scrape and sand peeled or checked paint to a sound surface. Sand glossy surfaces dull. Seal stains from water, smoke, ink, pencil, grease, etc. with the appropriate primer/sealer.

Aluminum and Galvanized Steel
Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method.

Cement Composition Siding/Panels
Remove all dirt, dust, grease, oil, loose particles, laitance, foreign material, and peeling or defective coatings. Allow the surface to dry thoroughly. If the surface is new, test it for pH, if the pH is higher than 8, prime with Loxon Concrete & Masonry Primer.



SUPERPAINT[®]

Exterior Latex High Gloss A85 Series

<u>SURFACE PREPARATION</u>	<u>SURFACE PREPARATION</u>	<u>CLEANUP INFORMATION</u>
<p>Masonry, Concrete, Cement, Block All new surfaces must be cured according to the supplier's recommendations—usually about 30 days. Remove all form release and curing agents. Rough surfaces can be filled to provide a smooth surface. If painting cannot wait 30 days, allow the surface to cure 7 days and prime the surface with Loxon Concrete & Masonry Primer. Cracks, voids, and other holes should be repaired with an elastomeric patch or sealant.</p> <p>Steel Rust and mill scale must be removed using sandpaper, wire brush, or other abrading method. Bare steel must be primed the same day as cleaned.</p> <p>Stucco Remove any loose stucco, efflorescence, or laitance. Allow new stucco to cure at least 30 days before painting. If painting cannot wait 30 days, allow the surface to dry 7 days and prime with Loxon Concrete & Masonry Primer. Repair cracks, voids, and other holes with an elastomeric patch or sealant.</p> <p>Vinyl Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly.</p> <p>Wood, Plywood, Composition Board Sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All patched areas must be primed.</p> <p>Caulking Gaps between windows, doors, trim, and other through-wall openings can be filled with the appropriate caulk after priming the surface.</p>	<p>Mildew Remove before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach/water solution.</p> <p style="text-align: center;"><u>APPLICATION</u></p> <p>Apply at temperatures above 50°F. No reduction needed.</p> <p>SuperPaint Exterior Latex High Gloss sets up very quickly, providing painted surfaces which resists sticking together (blocking). When used at normal temperature and humidity, windows and doors can be closed after 4 hours drying. Maximum blocking resistance is achieved after 24 hours. With this benefit, some adjustments to your painting approach must be made.</p> <ul style="list-style-type: none"> • Do not paint in direct sun. Temperatures over 80°F and humidity under 30% will make the paint set up quicker. • Do not over-work the product. Load paint on the surface, spread to cover, smooth out with long, even strokes. Finish this area before moving to a new area. Do not attempt to brush back into and further uniform an area once finished. • Work quickly to maintain a wet edge. • Paint objects in a vertical position to reduce the collection of airborne dirt and dust on the drying paint. <p>Brush Use a nylon/polyester brush.</p> <p>Roller 3/8" - 3/4" nap synthetic cover</p> <p>Spray—Airless Pressure2000 psi Tip......013"-.017"</p>	<p>Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.</p> <p style="text-align: center;"><u>CAUTIONS</u></p> <p>For exterior use only. Protect from freezing. Non-photochemically reactive. Not for use on floors.</p> <p>Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.</p> <p>HOTW 06/30/2015 A85W00051 22 90</p> <p>Viet, KOR</p> <p>The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative or visit www.paintdocs.com to obtain the most current version of the PDS and/or an SDS.</p>